

1N5518BUR-1 thru 1N5546BUR-1





Zener Diode Series, 500 mW

Rev. V2

Features

- 1N5518BUR-1 - 1N5546BUR-1 Available in JAN, JANTX and JANTXV PER MIL-PRF-19500/437
- Low Reverse Leakage Characteristics
- Leadless Package for Surface Mount
- Metallurgically Bonded
- Also available in DO-35 Axial Lead Glass Package.



Electrical Specifications: $T_A = +25^\circ\text{C}$ (unless otherwise specified)

JEDEC TYPE Number (Note 1)	Normal Zener Voltage V_z @ IZT	Zener Test Current IZT	Maximum Zener Impedance B-C-D Suffix ZZT @ IZT	Maximum Reverse Leakage Current			B-C-D Suffix Maximum DC Zener Current IZM	B-C-D Suffix Maximum Noise Density @ IZ=250 mA ND	Regulation Factor ΔV_Z (Note 2)	Low VZ Current IZL
				IR	VR = Volts					
	Volts	mA	Ohms	μA	NON & A- Suffix	B-C-D-Suffix	mA	$\mu\text{V} / \sqrt{\text{Hz}}$	Volts	mA
1N5518BUR-1	3.3	20	26	5.0	0.90	1.0	115	0.5	0.90	2.0
1N5519BUR-1	3.6	20	24	3.0	0.90	1.0	105	0.5	0.90	2.0
1N5520BUR-1	3.9	20	22	1.0	0.90	1.0	98	0.5	0.85	2.0
1N5521BUR-1	4.3	20	18	3.0	1.0	1.5	88	0.5	0.75	2.0
1N5522BUR-1	4.7	10	22	2.0	1.5	2.0	81	0.5	0.60	1.0
1N5523BUR-1	5.1	5.0	26	2.0	2.0	2.5	75	0.5	0.65	0.25
1N5524BUR-1	5.6	3.0	30	2.0	3.0	3.5	68	1.0	0.30	0.25
1N5525BUR-1	6.2	1.0	30	1.0	4.5	5.0	61	1.0	0.20	0.01
1N5526BUR-1	6.8	1.0	30	1.0	5.5	6.2	56	1.0	0.10	0.01
1N5527BUR-1	7.5	1.0	35	0.5	6.0	6.8	51	2.0	0.05	0.01
1N5528BUR-1	8.2	1.0	40	0.5	6.5	7.5	46	4.0	0.05	0.01
1N5529BUR-1	9.1	1.0	45	0.1	7.0	8.2	42	4.0	0.05	0.01
1N5530BUR-1	10.0	1.0	60	0.05	8.0	9.1	38	4.0	0.10	0.01
1N5531BUR-1	11.0	1.0	80	0.05	9.0	9.9	35	5.0	0.20	0.01
1N5532BUR-1	12.0	1.0	90	0.05	9.5	0.8	32	10	0.20	0.01
1N5533BUR-1	13.0	1.0	90	0.01	10.5	11.7	29	15	0.20	0.01
1N5534BUR-1	14.0	1.0	100	0.01	11.5	12.6	27	20	0.20	0.01
1N5535BUR-1	15.0	1.0	100	0.01	12.5	13.5	25	20	0.20	0.01

(Continued next page)

1N5518BUR-1 thru 1N5546BUR-1



Zener Diode Series, 500 mW

Rev. V2

Electrical Specifications: $T_A = +25^\circ\text{C}$ (unless otherwise specified)

JEDEC TYPE Number (Note1)	Normal Zener Voltage V_Z @ IZT	Zener Test Current IZT	Maximum Zener Impedance B-C-D Suffix ZZT @ IZT	Maximum Reverse Leakage Current			B-C-D Suffix Maximum DC Zener Current IZM	B-C-D Suffix Maximum Noise Density @ IZ=250 mA ND	Regulation Factor ΔV_Z (Note 2)	Low VZ Current IZL
				IR	VR = Volts					
	Volts	mA	Ohms	μA	NON & A- Suffix	B-C-D-Suffix	mA	$\mu\text{V} / \sqrt{\text{Hz}}$	Volts	mA
1N5536BUR-1	16.0	1.0	100	0.01	13.0	14.4	24	20	0.20	0.01
1N5537BUR-1	17.0	1.0	100	0.01	14.0	15.3	22	20	0.20	0.01
1N5538BUR-1	18.0	1.0	100	0.01	15.0	16.2	21	20	0.20	0.01
1N5539BUR-1	19.0	1.0	100	0.01	16.0	17.1	20	20	0.20	0.01
1N5540BUR-1	20.0	1.0	100	0.01	17.0	18.0	19	20	0.20	0.01
1N5541BUR-1	22.0	1.0	100	0.01	18.0	19.8	17	25	0.25	0.01
1N5542BUR-1	24.0	1.0	100	0.01	20.0	21.6	16	30	0.30	0.01
1N5543BUR-1	25.0	1.0	100	0.01	21.0	22.4	15	35	0.35	0.01
1N5544BUR-1	28.0	1.0	100	0.01	23.0	25.2	14	40	0.40	0.01
1N5545BUR-1	30.0	1.0	100	0.01	24.0	27.0	13	45	0.45	0.01
1N5546BUR-1	33.0	1.0	100	0.01	28.0	29.7	12	50	0.50	0.01

1. No Suffix type numbers are +20% with guaranteed limits for only VZ, IR, and VF. Units with "A" suffix are +10% with guaranteed limits for VZ, IR, and VF. Units with guaranteed limits for all six parameters are indicated by a "B" suffix for +5.0% units, "C" suffix for +2.0% and "D" suffix for +1.0%.
2. Zener voltage is measured with the device junction in thermal equilibrium at an ambient temperature of $25^\circ\text{C} \pm 3^\circ\text{C}$.
3. Zener impedance is derived by superimposing on IZT @ 60Hz rms a.c. current equal to 10% of IZT.
4. Reverse leakage currents are measured at VR as shown on the table.
5. ΔV_Z is the maximum difference between VZ at IZT and VZ at IZL measured with the device junction in thermal equilibrium.

Absolute Maximum Ratings

Parameter	Absolute Maximum
DC Power Dissipation	500 mW @ $T_L = +50^\circ\text{C}$
Forward Voltage	1.1 V @ 200 mA
DC Power Derating	10 mW / $^\circ\text{C}$ above $+125^\circ\text{C}$
Junction & Storage Temperature	-65°C to $+175^\circ\text{C}$



1N5518BUR-1 thru 1N5546BUR-1




Zener Diode Series, 500 mW

Rev. V2

Graphs



Outline Drawing



DESIGN DATA

CASE: DO-213AA, Hermetically sealed glass case. (MELF, SOD-80, LL34)

LEAD FINISH: Tin / Lead

THERMAL RESISTANCE: ($R_{\theta JEC}$): 100 °C/W maximum at L = 0 inch

THERMAL IMPEDANCE: ($Z_{\theta JX}$): 25 °C/W maximum

POLARITY: Diode to be operated with the banded (cathode) end positive.

MOUNTING SURFACE SELECTION: The Axial Coefficient of Expansion (COE) Of this Device is Approximately +6PPM/°C. The COE of the Mounting Surface System Should Be Selected To Provide A Suitable Match With This Device.

MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.