


Axial Lead Schottky Diode

Rev. V1

Features

- Low Forward Voltage: 550 mV @ $I_F = 1$ A
- High Reverse Breakdown Voltage: 30 V
- Hermetically Sealed Glass, DO-7
- Flexible Axial-lead Mounting Terminals
- RoHS* Compliant

Hermetically Sealed Glass, DO-7



Description

The 1N5819 silicon Schottky diode offers a large reverse breakdown voltage with low forward voltage. The die, which is passivated with an advanced high-reliability passivation for very fast settling time and low leakage current, is packaged in the industry standard DO-7 hermetically sealed axial leaded glass package.

This rugged device is capable of reliable operation in all military, commercial and industrial applications.

The 1N5819 is designed to be used in wide variety of applications, such as in high frequency rectifiers, reverse polarity protection and more.

Electrical Specifications: $T_A = +25^\circ\text{C}$

Parameter	Test Conditions	Units	Min.	Typ.	Max.
Reverse Breakdown Voltage (V_B)	$I_R = 10 \mu\text{A}$	V	30	—	—
Reverse Leakage Current (I_R)	$V_R = 30$ V, $T_A = +25^\circ\text{C}$ $V_R = 30$ V, $T_A = +100^\circ\text{C}$	μA mA	—	—	500 10
Forward Voltage (V_F)	$I_F = 1$ A	mV	—	550	—
Total Capacitance (C_T)	$V_R = 4$ V, 1 MHz	pF	—	110	—

Ordering Information^{1,2}

Part Number	Package
1N5819-R	3000 piece reel
1N5819-B	100 piece bulk in bag
1N5819-FP	50 piece per flat pack

* Restrictions on Hazardous Substances, European Union Directive 2011/65/EU.

Static and Moisture Sensitivity

These electronic devices are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these HBM Class 0 devices. The moisture sensitivity level is MSL 1.

Environmental Capabilities

These electronic devices are capable of meeting the environmental requirements of MIL-STD-750 and MIL-STD-883.

Axial Lead Schottky Diode


Rev. V1

Absolute Maximum Ratings^{1,2}

Parameter	Absolute Maximum
DC Power Dissipation	1.25 W Infinite heat sink, T _C = +25°C Derate power linearity from 1.25 W @ +25°C to 0 W @ +125°C
Average Rectified Forward Current	1 A
Reverse DC Voltage	30 V
Junction Temperature	+125°C
Operating Temperature	-65°C to +125°C
Storage Temperature	-65°C to +150°C
Assembly Temperature	+260°C, t = 10 sec.

1. Exceeding any one or combination of these limits may cause permanent damage to this device.
2. MACOM does not recommend sustained operation near these survivability limits.

Hermetically Sealed Glass, DO-7



Lead Material: copper clad steel
 Lead Finish: tin/lead
 Marking: part number and cathode band
 Weight: 0.2 grams
 Polarity: diode to be operated with the cathode band end negative
 Mounting Position: any


Axial Lead Schottky Diode

Rev. V1

Time-Temperature Profile for Sn 60 / Pb 40 or RoHS Type Solders

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Average ramp-up rate (TL to TP)	3°C/second maximum	3°C/second maximum
Preheat - Temperature Minimum (TSMIN) - Temperature Maximum (TSMAX) - Time (Minimum to maximum) (ts)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
TSMAX to TL - Ramp-up Rate	—	3°C/second maximum
Time Maintained above: - Temperature (TL) - Time (tL)	183°C 60-150 seconds	217°C 60-150 seconds
Peak Temperature (TP)	225 +0 / -5°C	260 +0 / -5°C
Time within 5°C of actual Peak Temperature (TP)	10-30 seconds	20-40 seconds
Ramp-down Rate	6°C/second maximum	6°C/second maximum
Time 25°C to Peak Temperature	6 minutes maximum	8 minutes maximum

Solder Re-Flow Time-Temperature Function



MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.