

1N957BUR-1 thru 1N986BUR-1



Silicon Zener Diode Series

Rev. V1

Features

- Available in JAN, JANTX and JANTXV per MIL-PRF-19500/117
- Standard voltage tolerances are plus/minus 5% with B suffix, 10% with A suffix identification.
- Tight tolerances available in plus or minus 2% or 1% with C or D suffix respectively.
- 500 mW power handling
- Hermetically sealed axial-leaded glass DO-213AA package.



Electrical Specifications: $T_A = +25^\circ\text{C}$ (unless otherwise specified)

Part # ¹	Normal Zener Voltage V_Z	Zener Test Current I_{ZT}	Max. Zener Impedance			Max. DC Zener Current I_{ZM}	Max. Surge Current I_{ZSM}	Max. Reverse Leakage $I_R @ V_R$		Max. Temperature Coefficient a_{V_Z}
	Volts	mA	$Z_{ZT} @ I_{ZT}$ Ohms	Z_{ZK} Ohms	@ I_{ZK} mA	mA	mA	mA	Volts	%/°C
1N957BUR-1	6.8	18.5	4.5	700	1.0	55	300	150	5.2	0.05
1N958BUR-1	7.5	16.5	5.5	700	0.5	50	275	75	5.7	0.058
1N959BUR-1	8.2	15.0	6.5	700	0.5	45	250	50	6.2	0.065
1N960BUR-1	9.1	14.0	7.5	700	0.5	41	225	25	6.9	0.068
1N961BUR-1	10	12.5	8.5	700	0.25	38	200	10	7.6	0.075
1N962BUR-1	11	11.5	9.5	700	0.25	32	175	5	8.4	0.076
1N963BUR-1	12	10.5	11.5	700	0.25	31	160	5	9.1	0.077
1N964BUR-1	13	9.5	13	700	0.25	28	150	5	9.9	0.079
1N965BUR-1	15	8.5	16	700	0.25	25	130	5	11.4	0.082
1N966BUR-1	16	7.8	17	700	0.25	24	120	5	12.2	0.083
1N967BUR-1	18	7.0	21	750	0.25	20	110	5	13.7	0.085
1N968BUR-1	20	6.2	25	750	0.25	18	100	5	15.2	0.086
1N969BUR-1	22	5.6	29	750	0.25	16	90	5	16.7	0.087
1N970BUR-1	24	5.2	33	750	0.25	15	80	5	18.2	0.088

1. The JEDEC type numbers shown (B Suffix) have a +5% tolerance on nominal Zener Voltage. The suffix A is used to identify +10% tolerance; suffix C is used to identify +2%; and suffix D is used to identify +1%; no suffix indicates +20%.

Continued on next page

1N957BUR-1 thru 1N986BUR-1



Silicon Zener Diode Series

Rev. V1

Electrical Specifications: $T_A = +25^\circ\text{C}$ (unless otherwise specified)

Part # ¹	Normal Zener Voltage V_Z	Zener Test Current I_{ZT}	Max. Zener Impedance			Max. DC Zener Current I_{ZM}	Max. Surge Current I_{ZSM}	Max. Reverse Leakage $I_R @ V_R$		Max. Temperature Coefficient a_{V_Z}
	Volts	mA	$Z_{ZT} @ I_{ZT}$ Ohms	Z_{ZK} Ohms	@ I_{ZK} mA	mA	mA	mA	Volts	%/ $^\circ\text{C}$
1N971BUR-1	27	4.6	41	750	0.25	13	70	5	20.6	0.090
1N972BUR-1	30	4.2	49	1000	0.25	12	65	5	22.8	0.091
1N973BUR-1	33	3.8	58	1000	0.25	11	60	5	25.1	0.092
1N974BUR-1	36	3.4	70	1000	0.25	10	55	5	27.4	0.093
1N975BUR-1	39	3.2	80	1000	0.25	9.5	46	5	29.7	0.094
1N976BUR-1	43	3.0	93	1000	0.25	8.8	44	5	32.7	0.095
1N977BUR-1	47	2.7	105	1500	0.25	7.9	40	5	35.8	0.095
1N978BUR-1	51	2.5	125	1500	0.25	7.4	37	5	38.8	0.096
1N979BUR-1	56	2.2	150	2000	0.25	6.8	35	5	42.6	0.096
1N980BUR-1	62	2.0	185	2000	0.25	6.0	30	5	47.1	0.097
1N981BUR-1	68	1.8	230	2000	0.25	5.5	28	5	51.7	0.097
1N982BUR-1	75	1.7	270	2000	0.25	5.0	26	5	56.0	0.098
1N983BUR-1	82	1.5	330	3000	0.25	4.6	23	5	62.2	0.098
1N984BUR-1	91	1.4	400	3000	0.25	4.1	21	5	69.2	0.099
1N985BUR-1	100	1.3	500	3000	0.25	3.7	18	5	76.0	0.11
1N986BUR-1	110	1.1	750	4000	0.25	3.3	16	5	83.6	0.11

1. The JEDEC type numbers shown (B Suffix) have a +5% tolerance on nominal Zener Voltage. The suffix A is used to identify +10% tolerance; suffix C is used to identify +2%; and suffix D is used to identify +1%; no suffix indicates +20%.

Absolute Maximum Ratings^{2,3}

Parameter	Absolute Maximum
Thermal Resistance	250 $^\circ\text{C}/\text{W}$
Steady-State Power	0.5 W
Forward Voltage	1.1 V @ 200 mA
Operating / Storage Temperature	-65 $^\circ\text{C}$ to +175 $^\circ\text{C}$

2. Exceeding any one or combination of these limits may cause permanent damage to this device.
 3. MACOM does not recommend sustained operation near these survivability limits.




FIGURE 1
POWER DERATING CURVE




FIGURE 2
ZENER VOLTAGE TEMPERATURE COEFFICIENT vs. ZENER VOLTAGE





FIGURE 3
CAPACITANCE vs. ZENER VOLTAGE

Outline (DO – 213AA, Hermetically sealed glass case. (MELF, SOD-80, LL34))



LEADED DESIGN DATA

CASE: DO – 213AA, Hermetically sealed glass case.
(MELF, SOD-80, LL34)

LEAD FINISH: Tin / Lead

POLARITY: Cathode end is banded.

MOUNTING POSITION: Any.

MOUNTING SURFACE SELECTION: The Axial Coefficient of Expansion (COE) Of this Device is Approximately +6 PPM/°C. The COE of the Mounting Surface System Should Be Selected To Provide A Suitable Match With This Device.

Dim.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
D	1.60	1.70	0.063	0.067
F	0.41	0.55	0.016	0.022
G	3.30	3.70	0.130	0.140
G1	2.54 ref.		0.100 ref.	
S	0.03 min.		0.001 min.	

MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.