

# 1N957BUR-1 thru 1N986BUR-1




## Silicon Zener Diode Series

Rev. V1

### Features

- Available in JAN, JANTX and JANTXV per MIL-PRF-19500/117
- Standard voltage tolerances are plus/minus 5% with B suffix, 10% with A suffix identification.
- Tight tolerances available in plus or minus 2% or 1% with C or D suffix respectively.
- 500 mW power handling
- Hermetically sealed axial-leaded glass DO-213AA package.



### Electrical Specifications: $T_A = +25^\circ\text{C}$ (unless otherwise specified)

| Part # <sup>1</sup> | Normal Zener Voltage $V_Z$ | Zener Test Current $I_{ZT}$ | Max. Zener Impedance      |                  |                  | Max. DC Zener Current $I_{ZM}$ | Max. Surge Current $I_{ZSM}$ | Max. Reverse Leakage $I_R @ V_R$ |       | Max. Temperature Coefficient $a_{V_Z}$ |
|---------------------|----------------------------|-----------------------------|---------------------------|------------------|------------------|--------------------------------|------------------------------|----------------------------------|-------|--|
|                     | Volts                      | mA                          | $Z_{ZT} @ I_{ZT}$<br>Ohms | $Z_{ZK}$<br>Ohms | @ $I_{ZK}$<br>mA | mA                             | mA                           | mA                               | Volts | %/°C                                   |
| 1N957BUR-1          | 6.8                        | 18.5                        | 4.5                       | 700              | 1.0              | 55                             | 300                          | 150                              | 5.2   | 0.05                                   |
| 1N958BUR-1          | 7.5                        | 16.5                        | 5.5                       | 700              | 0.5              | 50                             | 275                          | 75                               | 5.7   | 0.058                                  |
| 1N959BUR-1          | 8.2                        | 15.0                        | 6.5                       | 700              | 0.5              | 45                             | 250                          | 50                               | 6.2   | 0.065                                  |
| 1N960BUR-1          | 9.1                        | 14.0                        | 7.5                       | 700              | 0.5              | 41                             | 225                          | 25                               | 6.9   | 0.068                                  |
| 1N961BUR-1          | 10                         | 12.5                        | 8.5                       | 700              | 0.25             | 38                             | 200                          | 10                               | 7.6   | 0.075                                  |
| 1N962BUR-1          | 11                         | 11.5                        | 9.5                       | 700              | 0.25             | 32                             | 175                          | 5                                | 8.4   | 0.076                                  |
| 1N963BUR-1          | 12                         | 10.5                        | 11.5                      | 700              | 0.25             | 31                             | 160                          | 5                                | 9.1   | 0.077                                  |
| 1N964BUR-1          | 13                         | 9.5                         | 13                        | 700              | 0.25             | 28                             | 150                          | 5                                | 9.9   | 0.079                                  |
| 1N965BUR-1          | 15                         | 8.5                         | 16                        | 700              | 0.25             | 25                             | 130                          | 5                                | 11.4  | 0.082                                  |
| 1N966BUR-1          | 16                         | 7.8                         | 17                        | 700              | 0.25             | 24                             | 120                          | 5                                | 12.2  | 0.083                                  |
| 1N967BUR-1          | 18                         | 7.0                         | 21                        | 750              | 0.25             | 20                             | 110                          | 5                                | 13.7  | 0.085                                  |
| 1N968BUR-1          | 20                         | 6.2                         | 25                        | 750              | 0.25             | 18                             | 100                          | 5                                | 15.2  | 0.086                                  |
| 1N969BUR-1          | 22                         | 5.6                         | 29                        | 750              | 0.25             | 16                             | 90                           | 5                                | 16.7  | 0.087                                  |
| 1N970BUR-1          | 24                         | 5.2                         | 33                        | 750              | 0.25             | 15                             | 80                           | 5                                | 18.2  | 0.088                                  |

1. The JEDEC type numbers shown (B Suffix) have a +5% tolerance on nominal Zener Voltage. The suffix A is used to identify +10% tolerance; suffix C is used to identify +2%; and suffix D is used to identify +1%; no suffix indicates +20%.

Continued on next page

# 1N957BUR-1 thru 1N986BUR-1



## Silicon Zener Diode Series

Rev. V1

### Electrical Specifications: $T_A = +25^\circ\text{C}$ (unless otherwise specified)


| Part # <sup>1</sup> | Normal Zener Voltage $V_Z$ | Zener Test Current $I_{ZT}$ | Max. Zener Impedance      |                  |                  | Max. DC Zener Current $I_{ZM}$ | Max. Surge Current $I_{ZSM}$ | Max. Reverse Leakage $I_R @ V_R$ |       | Max. Temperature Coefficient $a_{V_Z}$ |
|---------------------|----------------------------|-----------------------------|---------------------------|------------------|------------------|--------------------------------|------------------------------|----------------------------------|-------|--|
|                     | Volts                      | mA                          | $Z_{ZT} @ I_{ZT}$<br>Ohms | $Z_{ZK}$<br>Ohms | @ $I_{ZK}$<br>mA | mA                             | mA                           | mA                               | Volts | %/ $^\circ\text{C}$                    |
| 1N971BUR-1          | 27                         | 4.6                         | 41                        | 750              | 0.25             | 13                             | 70                           | 5                                | 20.6  | 0.090                                  |
| 1N972BUR-1          | 30                         | 4.2                         | 49                        | 1000             | 0.25             | 12                             | 65                           | 5                                | 22.8  | 0.091                                  |
| 1N973BUR-1          | 33                         | 3.8                         | 58                        | 1000             | 0.25             | 11                             | 60                           | 5                                | 25.1  | 0.092                                  |
| 1N974BUR-1          | 36                         | 3.4                         | 70                        | 1000             | 0.25             | 10                             | 55                           | 5                                | 27.4  | 0.093                                  |
| 1N975BUR-1          | 39                         | 3.2                         | 80                        | 1000             | 0.25             | 9.5                            | 46                           | 5                                | 29.7  | 0.094                                  |
| 1N976BUR-1          | 43                         | 3.0                         | 93                        | 1000             | 0.25             | 8.8                            | 44                           | 5                                | 32.7  | 0.095                                  |
| 1N977BUR-1          | 47                         | 2.7                         | 105                       | 1500             | 0.25             | 7.9                            | 40                           | 5                                | 35.8  | 0.095                                  |
| 1N978BUR-1          | 51                         | 2.5                         | 125                       | 1500             | 0.25             | 7.4                            | 37                           | 5                                | 38.8  | 0.096                                  |
| 1N979BUR-1          | 56                         | 2.2                         | 150                       | 2000             | 0.25             | 6.8                            | 35                           | 5                                | 42.6  | 0.096                                  |
| 1N980BUR-1          | 62                         | 2.0                         | 185                       | 2000             | 0.25             | 6.0                            | 30                           | 5                                | 47.1  | 0.097                                  |
| 1N981BUR-1          | 68                         | 1.8                         | 230                       | 2000             | 0.25             | 5.5                            | 28                           | 5                                | 51.7  | 0.097                                  |
| 1N982BUR-1          | 75                         | 1.7                         | 270                       | 2000             | 0.25             | 5.0                            | 26                           | 5                                | 56.0  | 0.098                                  |
| 1N983BUR-1          | 82                         | 1.5                         | 330                       | 3000             | 0.25             | 4.6                            | 23                           | 5                                | 62.2  | 0.098                                  |
| 1N984BUR-1          | 91                         | 1.4                         | 400                       | 3000             | 0.25             | 4.1                            | 21                           | 5                                | 69.2  | 0.099                                  |
| 1N985BUR-1          | 100                        | 1.3                         | 500                       | 3000             | 0.25             | 3.7                            | 18                           | 5                                | 76.0  | 0.11                                   |
| 1N986BUR-1          | 110                        | 1.1                         | 750                       | 4000             | 0.25             | 3.3                            | 16                           | 5                                | 83.6  | 0.11                                   |

1. The JEDEC type numbers shown (B Suffix) have a +5% tolerance on nominal Zener Voltage. The suffix A is used to identify +10% tolerance; suffix C is used to identify +2%; and suffix D is used to identify +1%; no suffix indicates +20%.


### Absolute Maximum Ratings<sup>2,3</sup>

| Parameter                       | Absolute Maximum                              |
|---------------------------------|---|
| Thermal Resistance              | 250 $^\circ\text{C}/\text{W}$                 |
| Steady-State Power              | 0.5 W   |
| Forward Voltage                 | 1.1 V @ 200 mA                                |
| Operating / Storage Temperature | -65 $^\circ\text{C}$ to +175 $^\circ\text{C}$ |


2. Exceeding any one or combination of these limits may cause permanent damage to this device.  
 3. MACOM does not recommend sustained operation near these survivability limits.



**FIGURE 1**  
POWER DERATING CURVE



**FIGURE 2**  
ZENER VOLTAGE TEMPERATURE COEFFICIENT vs. ZENER VOLTAGE



**FIGURE 3**  
CAPACITANCE vs. ZENER VOLTAGE


# 1N957BUR-1 thru 1N986BUR-1



## Silicon Zener Diode Series

Rev. V1

Outline (DO – 213AA, Hermetically sealed glass case. (MELF, SOD-80, LL34))



### LEADED DESIGN DATA

CASE: DO – 213AA, Hermetically sealed glass case.  
(MELF, SOD-80, LL34)

LEAD FINISH: Tin / Lead

POLARITY: Cathode end is banded.

MOUNTING POSITION: Any.

MOUNTING SURFACE SELECTION: The Axial Coefficient of Expansion (COE) Of this Device is Approximately +6 PPM/°C. The COE of the Mounting Surface System Should Be Selected To Provide A Suitable Match With This Device.

| Dim. | Millimeters |      | Inches     |       |
|------|-------------|------|------------|-------|
|      | Min.        | Max. | Min.       | Max.  |
| D    | 1.60        | 1.70 | 0.063      | 0.067 |
| F    | 0.41        | 0.55 | 0.016      | 0.022 |
| G    | 3.30        | 3.70 | 0.130      | 0.140 |
| G1   | 2.54 ref.   |      | 0.100 ref. |       |
| S    | 0.03 min.   |      | 0.001 min. |       |

MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.