

2N2221A, L, UA, UB & 2N2222A, L, UA, UB




Radiation Hardened NPN Silicon Switching Transistors

Rev. V1

Features

- Qualified to MIL-PRF-19500/255
- Levels
 - JANSM-3K Rads (Si) JAN
 - JANSD-10K Rads (Si) JANTX
 - JANSP-30K Rads (Si) JANTXV
 - JANSL-50K Rads (Si) JAN
 - JANSR-100K Rads (Si)
- TO-18 (TO-206AA), Surface mount UA & UB Packages



Applications

- Switching and Linear Applications
- DC and VHF Amplifier Applications

Electrical Specifications @ $T_A = 25^\circ\text{C}$

Parameter	Test Conditions	Symbol	Units	Minimum	Maximum	
Off Characteristics:						
Collector - Emitter Breakdown	$I_C = 10 \text{ mAdc}$	$V_{(BR)CEO}$	Vdc	50	—	
Collector - Base Cutoff Current	$V_{CB} = 75 \text{ Vdc}$	I_{CBO1}	μAdc	—	10	
	$V_{CB} = 60 \text{ Vdc}$	I_{CBO2}	nAdc	—	10	
Emitter - Base Cutoff Current	$V_{EB} = 6.0 \text{ Vdc}$	I_{EBO1}	μAdc	—	10	
	$V_{EB} = 4.0 \text{ Vdc}$	I_{EBO2}	nAdc	—	10	
Collector - Emitter Cutoff Current	$V_{CE} = 50 \text{ Vdc}$	I_{CES}	nAdc	—	50	
On Characteristics¹:						
Forward Current Transfer Ratio	2N2221A, L, UA, UB		hFE			
	$I_C = 0.1 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$			30	—	
	$I_C = 1.0 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$			35	150	
	$I_C = 10.0 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$			40	—	
	$I_C = 150.0 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$			40	120	
	$I_C = 500.0 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$			20	—	
	2N2222A, L, UA, UB					
	$I_C = 0.1 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$			50	—	
	$I_C = 1.0 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$			75	325	
	$I_C = 10.0 \text{ mAdc}, V_{CE} = 10 \text{ Vdc}$			100	11	
Collector - Base Cutoff Current	$I_C = 150 \text{ mAdc}, I_B = 15 \text{ mAdc}$	$V_{CE(sat)}$	Vdc	—	0.3	
	$I_C = 500 \text{ mAdc}, I_B = 50 \text{ mAdc}$				1.0	
Base - Emitter Saturation Voltage	$I_C = 150 \text{ mAdc}, I_B = 15 \text{ mAdc}$	$V_{BE(sat)}$	Vdc	0.6	1.2	
	$I_C = 500 \text{ mAdc}, I_B = 50 \text{ mAdc}$			—	2.0	

1. Pulse Test: Pulse Width = 300 ms, Duty Cycle < 2%.

(Continued next page)

2N2221A, L, UA, UB & 2N2222A, L, UA, UB



Radiation Hardened NPN Silicon Switching Transistors

Rev. V1

Electrical Specifications @ $T_A = 25^\circ\text{C}$

Parameter	Test Conditions	Symbol	Units	Minimum	Maximum
Dynamic Characteristics:					
Small-Signal Short-Circuit Forward Current Transfer Ratio	$I_C = 1 \text{ mAdc}$, $V_{CE} = 10 \text{ Vdc}$, $f = 1 \text{ kHz}$ 2N2221A, L, UA, UB 2N2222A, L, UA, UB	hfe		30 50	—
Magnitude of Small-Signal Short-Circuit, Forward Current Transfer Ratio	$I_C = 20 \text{ mAdc}$, $V_{CE} = 20 \text{ Vdc}$, $f = 100 \text{ MHz}$	hfe		2.5	—
Output Capacitance	$V_{CB} = 10 \text{ Vdc}$, $I_E = 0$, $100 \text{ kHz} \leq f \leq 1 \text{ MHz}$ $V_{CB} = 0.5 \text{ Vdc}$, $I_E = 0$, $100 \text{ kHz} \leq f \leq 1 \text{ MHz}$	C_{OBO} C_{1BO}	pF	—	8 25
Switching Characteristics:					
Turn-On Time	(See figure 17 of MIL-PRF-19500/255)	T_{ON}	ns	—	35
Turn-Off Time	(See Figure 18 of MIL-PRF-19500/255)	T_{OFF}	ns	—	300

Absolute Maximum Ratings @ $T_C = 25^\circ\text{C}$

Parameter	Absolute Maximum
Collector - Emitter Voltage (V_{CEO})	50 Vdc
Collector - Base Voltage (V_{CBO})	75 Vdc
Emitter - Base Voltage (V_{EBO})	6.0 Vdc
Collector Current (I_C)	800 mAdc
Total Power Dissipation (P_T) $T_A = +25^\circ\text{C}$	0.5 W
Thermal Resistance ($R_{\theta JC}$) Junction to Ambient	325 $^\circ\text{C/W}$
Operating Temperature	-65 $^\circ\text{C}$ to +200 $^\circ\text{C}$
Storage Temperature	-65 $^\circ\text{C}$ to +200 $^\circ\text{C}$


2N2221A, L, UA, UB & 2N2222A, L, UA, UB



Radiation Hardened NPN Silicon Switching Transistors

Rev. V1

Outline Drawing (TO-18):



Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min.	Max.	Min.	Max.	
CD	0.178	0.195	4.52	1.95	—
CH	0.170	0.210	4.32	5.33	—
HD	0.209	0.230	5.31	5.84	—
LC	0.100 Typ.		2.54 Typ		6
LD	0.016	0.021	0.41	0.53	7, 8
LL	0.500	0.750	12.70	19.05	7, 8, 13
LU	0.016	0.019	0.41	0.48	7, 8
L1	—	0.050	—	1.27	7, 8
L2	0.250	—	6.35	—	7, 8
P	0.100	—	2.54	—	—
Q	—	0.030	—	0.76	5
TL	0.028	0.048	0.71	1.22	3, 4
TW	0.036	0.046	0.91	1.17	3
r	—	0.010	—	0.25	10
a	45° Typ.				6
1, 2, 9, 11, 12, 13					

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Beyond r (radius) maximum, TL shall be held for a minimum length of .011 inch (0.28 mm).
4. Dimension TL measured from maximum HD.
5. Body contour optional within zone defined by HD, CD, and Q.
6. Leads at gauge plane .054 +.001 -.000 inch (1.37 +0.03 -0.00 mm) below seating plane shall be within 0.007 inch (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC.
7. Dimension LU applies between L1 and L2. Dimension LD applies between L2 and LL minimum. Diameter is uncontrolled in L1 and beyond LL minimum.
8. All three leads.
9. The collector shall be internally connected to the case.
10. Dimension r (radius) applies to both inside corners of tab.
11. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.
12. Lead 1 = emitter, lead 2 = base, lead 3 = collector.
13. For L suffix devices, dimension LL = 1.5 inches (38.10 mm) min. and 1.75 inches (44.45 mm) max.


2N2221A, L, UA, UB & 2N2222A, L, UA, UB



Radiation Hardened NPN Silicon Switching Transistors

Rev. V1

Outline Drawing (UA Surface Mount):



Pin #	1	2	3	4
Transistor	Collector	Emitter	Base	N/C

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min.	Max.	Min.	Max.	
BL	0.215	0.225	5.46	5.71	—
BL2	—	0.225	—	5.71	—
BW	0.145	0.155	3.68	3.93	—
BW2	0.155		3.93		—
CH	0.061	0.075	1.55	1.90	3
L3	0.003	0.007	0.08	0.18	5
LH	0.029	0.042	0.74	1.07	—
LL1	0.032	0.048	0.81	1.22	—
LL2	0.072	0.088	1.83	2.23	—
LS	0.045	0.055	1.14	1.39	—
LW	0.022	0.028	0.56	0.71	—
LW2	0.006	0.022	0.15	0.56	5

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Dimension CH controls the overall package thickness. When a window lid is used, dimension CH must increase by a minimum of .010 inch (0.254 mm) and a maximum of .040 inch (1.020 mm).
4. The corner shape (square, notch, radius) may vary at the manufacturer's option, from that shown on the drawing.
5. Dimensions LW2 minimum and L3 minimum and the appropriate castellation length define an unobstructed three-dimensional space traversing all of the ceramic layers in which a castellation was designed. (Castellations are required on the bottom two layers, optional on the top ceramic layer.) Dimension LW2 maximum and L3 maximum define the maximum width and depth of the castellation at any point on its surface. Measurement of these dimensions may be made prior to solder dipping.
6. The co-planarity deviation of all terminal contact points, as defined by the device seating plane, shall not exceed .006 inch (0.15 mm) for solder dipped leadless chip carriers.
7. In accordance with ASME Y14.5M, diameters are equivalent to Φ x symbology.



2N2221A, L, UA, UB & 2N2222A, L, UA, UB



Radiation Hardened NPN Silicon Switching Transistors

Rev. V1

Outline Drawing (UB Surface Mount):



Symbol	Dimensions			
	Inches		Millimeters	
	Min.	Max.	Min.	Max.
BH	0.046	0.056	1.17	1.42
BL	0.115	0.128	2.92	3.25
BW	0.085	0.108	2.16	2.74
CL	—	0.128		3.25
CW		0.108		2.74
LL1	0.022	0.038	0.56	0.96
LL2	0.017	0.035	0.43	0.89
LS1	0.036	0.040	0.91	1.02
LS2	0.071	0.079	1.81	2.01
LW	0.016	0.024	0.41	0.61
r	—	0.008	—	0.203
r1	—	0.012	—	0.305
r2	—	0.022	—	0.559

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Hatched areas on package denote metalized areas.
4. Pad 1 = Base, Pad 2 = Emitter, Pad 3 = Collector, Pad 4 = Shielding connected to the lid.
5. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.

2N2221A, L, UA, UB & 2N2222A, L, UA, UB



Radiation Hardened NPN Silicon Switching Transistors

Rev. V1

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.