


Features

- Available in JAN, JANTX, JANTXV per MIL-PRF-19500/545
- TO-5 Package: 2N3867, 2N3868
- TO-39 (TO-205AD) Package: 2N3867S, 2N3868S



Electrical Characteristics

Parameter	Test Conditions	Symbol	Units	Min.	Max.
Off Characteristics					
Collector - Base Breakdown Voltage	$I_C = 100 \mu\text{Adc}$, 2N3867, 2N3867S $I_C = 100 \mu\text{Adc}$, 2N3868, 2N3868S	$V_{(BR)CEO}$	Vdc	40 60	—
Collector - Emitter Breakdown Voltage	$I_C = 20 \text{ mAdc}$, 2N3867, 2N3867S $I_C = 20 \text{ mAdc}$, 2N3868, 2N3868S	$V_{(BR)CEO}$	Vdc	40 60	—
Emitter - Base Breakdown Voltage	$I_C = 100 \text{ mAdc}$	$V_{(BR)EBO}$	Vdc	40	—
Collector - Emitter Cutoff Current	$V_{EB} = 2 \text{ Vdc}$, $V_{CE} = 40 \text{ Vdc}$, 2N3867, 2N3867S $V_{EB} = 2 \text{ Vdc}$, $V_{CE} = 60 \text{ Vdc}$, 2N3868, 2N3868S	I_{CEX}	μAdc	—	1.0 1.0
Collector - Base Cutoff Current	$V_{CB} = 60 \text{ Vdc}$, 2N3867, 2N3867S $V_{CB} = 80 \text{ Vdc}$, 2N3868, 2N3868S	I_{CEO}	μAdc	—	100
Emitter - Base Cutoff Current	$V_{EB} = 4.0 \text{ Vdc}$	I_{EBO}	μAdc	—	100
On Characteristics¹					
Forward Current Transfer Ratio	$I_C = 500 \text{ mAdc}$, $V_{CE} = 1 \text{ Vdc}$, 2N3867, 2N3867S 2N3868, 2N3868S $I_C = 1.5 \text{ Adc}$, $V_{CE} = 2 \text{ Vdc}$, 2N3867, 2N3867S 2N3868, 2N3868S $I_C = 2.5 \text{ Adc}$, $V_{CE} = 3 \text{ Vdc}$, 2N3867, 2N3867S 2N3868, 2N3868S $I_C = 3.0 \text{ mAdc}$, $V_{CE} = 5 \text{ Vdc}$, All Types	H_{FE}	-	50 35 40 30 25 20 20	— — 200 150 — — —
Collector - Emitter Saturation Voltage	$I_C = 500 \text{ mAdc}$, $I_B = 50 \text{ mAdc}$ $I_C = 1.5 \text{ Adc}$, $I_B = 150 \text{ mAdc}$ $I_C = 2.5 \text{ Adc}$, $I_B = 250 \text{ mAdc}$	$V_{CE(SAT)}$	Vdc	—	0.50 0.75 1.50
Base - Emitter Saturation Voltage	$I_C = 500 \text{ mAdc}$, $I_B = 50 \text{ mAdc}$ $I_C = 1.5 \text{ Adc}$, $I_B = 150 \text{ mAdc}$ $I_C = 2.5 \text{ Adc}$, $I_B = 250 \text{ mAdc}$	$V_{BE(SAT)}$	Vdc	—	1.0 1.4 2.0

1. Pulse Test: Pulse Width = 300 μs , Duty Cycle $\leq 2.0\%$.

PNP Power Silicon Transistor

Rev. V1

Electrical Characteristics

Parameter	Test Conditions	Symbol	Units	Min.	Max.
Dynamic Characteristics					
Magnitude of Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio	$I_C = 100 \text{ mAdc}, V_{CE} = 5.0 \text{ Vdc}, f = 20 \text{ MHz}$	$ h_{FE} $	-	3	12
Output Capacitance	$V_{CB} = 10 \text{ Vdc}, I_E = 0, 100 \text{ kHz} \leq f \leq 1 \text{ MHz}$	C_{OBO}	pF	—	120
Input Capacitance	$V_{CB} = 3 \text{ Vdc}, I_E = 0, 100 \text{ kHz} \leq f \leq 1 \text{ MHz}$	C_{IBO}	pF	—	800
Switching Characteristics					
Delay Time	$V_{CC} = -30 \text{ Vdc}, V_{EB} = 0$	T_D	ns	—	35
Rise Time	$I_C = 1.5 \text{ Adc}, I_{B1} = 150 \text{ mAdc}$	T_R	ns	—	65
Storage Time	$V_{CC} = -30 \text{ Vdc}, V_{EB} = 0$	T_S	ns	—	500
Fall Time	$I_C = 1.5 \text{ Adc}, I_{B1} = 150 \text{ mAdc}$	T_F	ns	—	100
Turn-On Time	$V_{CC} = 30, I_C = 1.5 \text{ Adc}, I_B = 150 \text{ mAdc}$	T_{ON}	ns	—	100
Turn-Off Time	$V_{CC} = 30, I_C = 1.5 \text{ Adc}, I_B = 150 \text{ mAdc}$	T_{OFF}	ns	—	100
Safe Operating Area					
DC Tests:	$T_C = +25^\circ\text{C}, 1 \text{ Cycle}, t = 1.0 \text{ s}$				
Test 1:	$V_{CE} = 3.3 \text{ Vdc}, I_C = 3 \text{ Adc}$				
Test 2:	$V_{CE} = 40 \text{ Vdc}, I_C = 160 \text{ mAdc}, 2\text{N}3867, 2\text{N}3867\text{S}$				
Test 3:	$V_{CE} = 60 \text{ Vdc}, I_C = 80 \text{ mAdc}, 2\text{N}3868, 2\text{N}3868\text{S}$				

Absolute Maximum Ratings

Ratings	Symbol	Value
Collector - Emitter Voltage 2N3867, 2N3867S 2N3868, 2N3868S	V_{CEO}	40 Vdc 60 Vdc
Collector - Base Voltage 2N3867, 2N3867S 2N3868, 2N3868S	V_{CBO}	40 Vdc 60 Vdc
Emitter - Base Voltage	V_{EBO}	4 Vdc
Collector Current	I_C	3 Adc
Total Power Dissipation @ $T_A = 25^\circ\text{C}^2$ @ $T_C = 25^\circ\text{C}^3$	P_T	1 W 10 W
Operating & Storage Temperature Range	T_{OP}, T_{STG}	-55°C to +200°C

- Derate linearly 5.71 mW / °C for $T_A > +25^\circ\text{C}$.
- Derate linearly 57.1 mW / °C for $T_C > +25^\circ\text{C}$.

Thermal Characteristics

Characteristics	Symbol	Max. Value
Thermal Resistance, Junction to Case	$R_{\theta JC}$	17.5°C/W

2


MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit www.macom.com for additional data sheets and product information.

For further information and support please visit:
<https://www.macom.com/support>

DC-0015127


Outline Drawings

TO-5 Package (2N3867S, 2N3868S)



Dimensions are in inches.

TO-39 (TO-205AD) Package (2N3867, 2N3868)



Dimensions are in inches.

MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.