

Features

- 4x25 Gbps CWDM AWG Chips With and Without Fiber Pigtail
- Low Insertion Loss
- High Reliability
- Custom Design: chip size, optical specifications, AR coating, polishing angles
- RoHS* Compliant
- Datacom 100G CWDM4 Applications

Mechanical Specification¹

Mechanical	Size
Chip Size	4 x 10 mm
Pitch	1100 μ m

1. Customized size and pitch available upon request.

Optical Specifications

Parameter	Conditions	Units	Min.	Typ.	Max.
Number of Channels (CH)	—	—	—	4	—
Spectral Region (SR)	O-Band	nm	1260	—	1360
Channel Wavelengths (λ_c)	measured @ 3 dB center CH1 CH2 CH3 CH4	nm	—	1271 1291 1311 1331	—
Channel Spacing (CS)	ITU-G.694.2	nm	—	20	—
Center Wavelength Accuracy ($\Delta\lambda$)	—	nm	—	+/-1	—
Insertion Loss ² (IL)	@ peak transmission	dB	—	—	3.0
1dB Bandwidth (δ_{1dB})	1 dB down from minimum IL	nm	11	—	—
Polarization Dependent Loss (PDL)	over all polarization states	dB	—	—	0.5
Polarization Mode Dispersion (PMD)	guaranteed by design	ps	—	—	0.15

2. Insertion loss will be 0.5 dB higher for the fiber pigtail, from the optical specification.

Ordering Information

Part Number	Package
A0425-MXX-C-x ³	polished chips
A0425-MXX-P-x ³	pigtailed chips

3. The -x variant will be used for customer specific specifications. Contact MACOM customer support for ordering options.

Absolute Maximum Ratings

Parameter	Absolute Maximum
Power	300 mW, each facet
Operating Temperature	-5°C to +75°C
Storage Temperature	-40°C to +85°C

* Restrictions on Hazardous Substances, European Union Directive 2011/65/EU.

MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.