

Features


- All Junctions Completely Protected with Silicon Dioxide
- 6.4 V Zener $\pm 5\%$
- Electrically Equivalent to 1N4565 - 1N4584A

Description

These 0.5 W zener diodes are electrically equivalent to the 1N4565 - 1N4584A series diodes. They are compatible with all wire bonding and die attach techniques with the exception of solder reflow.

These diodes are available in JANHC and JANKC per MIL-PRF-19500/452.

Die



Electrical Specifications: $T_A = +25^\circ\text{C}$

Part #	Zener Test Current I_{ZT}	Effective Temperature Coefficient	Max. Voltage Temperature Stability ΔV_{ZT} -55° to $+100^\circ$ (Note 2)	Temperature Range	Max. Zener Impedance Z_{ZT} (Note 1)
	mA	%/°C	mV	°C	Ohms
CD4565	0.5	0.01	48	0 to +75	200
CD4565A	0.5	0.01	100	-55 to +100	200
CD4566	0.5	0.005	24	0 to +75	200
CD4566A	0.5	0.005	50	-55 to +100	200
CD4567	0.5	0.002	10	0 to +75	200
CD4567A	0.5	0.002	20	-55 to +100	200
CD4568	0.5	0.001	5	0 to +75	200
CD4568A	0.5	0.001	10	-55 to +100	200
CD4569	0.5	0.0005	2.5	0 to +75	200
CD4569A	0.5	0.0005	5	-55 to +100	200
CD4570	1.0	0.01	48	0 to +75	100
CD4570A	1.0	0.01	100	-55 to +100	100
CD4571	1.0	0.005	24	0 to +75	100
CD4571A	1.0	0.005	50	-55 to +100	100
CD4572	1.0	0.002	10	0 to +75	100
CD4572A	1.0	0.002	20	-55 to +100	100
CD4573	1.0	0.001	5	0 to +75	100
CD4573A	1.0	0.001	10	-55 to +100	100

(Continued next page)

1 * Restrictions on Hazardous Substances, European Union Directive 2011/65/EU.

Electrical Specifications: $T_A = +25^\circ\text{C}$

Part #	Zener Test Current I_{ZT}	Effective Temperature Coefficient	Max. Voltage Temperature Stability ΔV_{ZT} -55° to +100° (Note 2)	Temperature Range	Max. Zener Impedance Z_{ZT} (Note 1)
	mA	%/°C	mV	°C	Ohms
CD4574	1.0	0.0005	2.5	0 to +75	100
CD4574A	1.0	0.0005	5	-55 to +100	100
CD4575	2.0	0.01	48	0 to +75	50
CD4575A	2.0	0.01	100	-55 to +100	50
CD4576	2.0	0.005	24	0 to +75	50
CD4576A	2.0	0.005	50	-55 to +100	50
CD4577	2.0	0.002	10	0 to +75	50
CD4577A	2.0	0.002	20	-55 to +100	50
CD4578	2.0	0.001	5	0 to +75	50
CD4578A	2.0	0.001	10	-55 to +100	50
CD4579	2.0	0.0005	2.5	0 to +75	50
CD4579A	2.0	0.0005	5	-55 to +100	50
CD4580	4.0	0.01	48	0 to +75	25
CD4580A	4.0	0.01	100	-55 to +100	25
CD4581	4.0	0.005	24	0 to +75	25
CD4581A	4.0	0.005	50	-55 to +100	25
CD4582	4.0	0.002	10	0 to +75	25
CD4582A	4.0	0.002	20	-55 to +100	25
CD4583	4.0	0.001	5	0 to +75	25
CD4583A	4.0	0.001	10	-55 to +100	25
CD4584	4.0	0.0005	2.5	0 to +75	25
CD4584A	4.0	0.0005	5	-55 to +100	25



1. Zener impedance is derived by superimposing on I_{ZT} a 60 Hz rms AC current equal to 10% of I_{ZT} .
2. The maximum allowable change observed over the entire temperature range i.e., the diode voltage will not exceed the specialized mV at any discrete temperature between the established limits, per JEDEC standard No.5.

Absolute Maximum Ratings^{5,6}


Parameter	Absolute Maximum
Reverse Leakage Current	$I_R = 2 \mu\text{A}$, $V_R = 3 V_{DC}$
Operating Temperature	-65°C to +175°C
Storage Temperature	-65°C to +175°C

- Exceeding any one or combination of these limits may cause permanent damage to this device.
- MACOM does not recommend sustained operation near these survivability limits.

Zener Impedance vs. Operating Current



Typical Change of Temperature Coefficient with Change in Operating Current




CD4565 thru CD4584A



TC Zener Diode Chip Series

Rev. V1

Die



M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.