


Features

- Available as JANHCE and JANKCE per MIL-PRF-19500/477
- Electrically equivalent to 1N5807, 1N5809 and 1N5811
- Passivated junction
- Compatible with all wire bonding and die attach techniques with the exception of solder reflow



TYPE	V_R	$V_{BR} @ 100 \mu A$	I_O $T_J = 75^\circ C$
CD5807	50 V	60 V	6.0 A
CD5809	100 V	110 V	6.0 A
CD5811	150 V	160 V	6.0 A

Electrical Characteristics:

CHARACTERISTIC	SYMBOL	MAXIMUM	UNITS
Reverse Current Rated $V_R, T_C = 25^\circ C$	I_R	5	μA
Reverse Current Rated $V_R, T_C = 125^\circ C$	I_R	525	μA
Forward Voltage Drop, $I_F = 4A, T_C = 25^\circ C$	V_F	0.875	Volts
Junction Capacitance @ $V_R = 10V$	C_j	60	pF

Reverse Recovery Characteristics:

CHARACTERISTIC	SYMBOL	MAXIMUM	UNITS
Reverse Recovery Time $I_F = 1A, I_{RM} = 1A, I_{(REC)} = 0.1A$	T_{rr}	30	ns
Forward Recovery Voltage @ 500 mA $T_r = 8$ ns	$V_{(Peak)}$	2.2	V
Forward Recovery Time, $I_F = 500$ mA	- - -	15	ns

CD5807, CD5809 & CD5811



Rectifier Diode Chips
Ultrafast Recovery


Rev. V1

Group A Electricals:

DRAWING NUMBER: MIL-S-19500/477, NUMBER: JANHCE1N5807/5809/5811, JANKCE1N5807/5809/5811

SYMBOL	TEST CONDITIONS	MINIMUM	MAXIMUM	UNIT
V _{FM1}	I _{FM} = 3.0 A, T _p = 8.3 ms (maximum)		0.865	V
V _{FM2}	I _{FM} = 4.0 A, T _p = 8.3 ms (maximum)		0.875	V
V _{FM3}	I _{FM} = 6.0 A, T _p = 8.3 ms (maximum)		0.925	V
I _{R1}	V _R = 50 V (CD5807) V _R = 100 V (CD5809) V _R = 150 V (CD5811)		5.0	μA
V _{(BR)1}	I _(BR) = 100 μA, T _p = 20 mS (maximum)	CD5807 CD5809 CD5811	60 110 160	V V V
I _{R2}	V _R = 50 V (CD5807) V _R = 100 V (CD5809) V _R = 150 V (CD5811)	T _A = +125 °C	525	μA
V _{FM4}	I _{FM} = 4.0 A, T _A = +125 °C, T _p = 8.3 mS (maximum)		0.830	V
V _{FM5}	I _{FM} = 4.0 A, T _A = -65 °C, T _p = 8.3 mS (maximum)		1.075	V
V _{(BR)2}	I _(BR) = 100 μA, T _A = -65 °C, T _p = 20 ms (maximum)	CD5807 CD5809 CD5811	50 100 150	V V V
t _{rr}	I _F = I _{FM} = 1.0 A, I _{RM} (REC) = 0.1 A, di/dt = 100 A/us (minimum)		30	nS
C _J	V _R = 10 V, f = 1 MHz, V _{sig} = 50 mV (P-P) (maximum)		60	pF
V _{FRM}	t _r = 8 nS, I _{FM} = 500 mA		2.2	V
t _{fr}	t _p ≥ 20 nS, t _r = 8 nS, V _{FR} = 1.1 x V _F , I _{FM} = 500 mA		15	nS

Outline Drawing



Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A	.068	.072	1.73	1.83
B	.057	.061	1.45	1.55
C	.008	.012	0.20	0.30

Notes:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.