

Features

- 8 W Power Amplifier
- 20 dB Small Signal Gain
- 39 dBm Saturated Pulsed Output Power
- Dual Sided Bias Architecture
- 100% On-wafer DC & RF Power Tested
- 100% Visual Inspection to MIL-STD-833
- Bare Die


Description

The MAAP-015024 three stage 14.5 - 17.5 GHz GaAs MMIC power amplifier has a saturated pulsed output power of 39 dBm and a small signal gain of 20 dB. The power amplifier must be biased directly on both sides of the die.

This MMIC uses MACOM's GaAs pHEMT device technology and is based upon optical gate lithography to ensure high repeatability and uniformity. The chip has surface passivation for protection and backside via holes and gold metallization to allow a conductive epoxy die attach process.

This device is well suited for communication and radar applications.

Functional Schematic



Pad Configuration

Pad No.	Function	Description
1	V _{G1}	1 st Stage Gate Voltage
3	V _{D1}	1 st Stage Drain Voltage
6	V _{G2}	2 nd Stage Gate Voltage
9	V _{D2}	2 nd Stage Drain Voltage
11	V _{G3}	3 rd Stage Gate Voltage
13	V _{D3}	3 rd Stage Drain Voltage
14	RF _{OUT}	RF Output
15	V _{D3}	3 rd Stage Drain Voltage
17	V _{G3}	3 rd Stage Gate Voltage
19	V _{D2}	2 nd Stage Drain Voltage
22	V _{G2}	2 nd Stage Gate Voltage
25	V _{D1}	1 ST Stage Drain Voltage
27	V _{G1}	1 st Stage Gate Voltage
28	RF _{IN}	RF Input

* Restrictions on Hazardous Substances, European Union Directive 2002/95/EC.

Electrical Specifications:

Freq. = 14.5 - 17.5 GHz, $T_A = +25^\circ\text{C}$, Duty Cycle = 5%, $P_{IN} = 23\text{ dBm}$

Parameter	Units	Min.	Typ.	Max.
Gain	dB	—	21.0	—
Gain Flatness	dB	—	+/-1.0	—
Input Return Loss	dB	—	10.0	—
Output Return Loss	dB	—	6.0	—
Reverse Isolation	dB	—	50.0	—
Saturated Output Power 14.5 - 15.0 GHz 15.0 - 17.5 GHz	dBm	35.0 37.5	37.5 39.0	—
Drain Bias Voltage	V	—	8.0	—
Gate Bias Voltage	V	—	-0.9	—
Current	A	—	5.0	7.0

Absolute Maximum Ratings^{1,2}

Parameter	Absolute Maximum
Input Power	+30 dBm
Gate Voltage	-0.5 V < V_G < -2 V
Supply Voltage	+8.5 Vdc
Supply Current	7.5 A
Storage Temperature	-65°C to +165°C
Operating Temperature	-40°C to +85°C
Junction Temperature ³	+175°C

1. Exceeding any one or combination of these limits may cause permanent damage to this device.
2. MACOM does not recommend sustained operation near these survivability limits.
3. Operating at nominal conditions with $T_J \leq +175^\circ\text{C}$ will ensure $\text{MTTF} > 1 \times 10^6$ hours.


Handling Procedures

Please observe the following precautions to avoid damage:


Static Sensitivity

Gallium Arsenide Integrated Circuits are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these devices.


Bonding Diagram



Schematic




MMIC Bare Die




Typical Performance Curves


Gain vs. Frequency




Reverse Isolation vs. Frequency




Input Return Loss vs. Frequency




Output Return Loss vs. Frequency



Output Power vs. Frequency, $V_G = -0.9$ V, $V_D = 8$ V




Current vs. Frequency, $V_G = -0.9$ V, $V_D = 8$ V




Typical Performance Curves


Gain vs. Output Power




Gain @ 14.5 GHz vs. Output Power




Gain @ 15.0 GHz vs. Output Power



Gain @ 15.5 GHz vs. Output Power



PAE vs. Output Power



Applications Section

Application Notes

Note 1 - Biasing

The MAAP-015024 is biased directly through the gates (V_{G1} , V_{G2} and V_{G3}) of the power amplifier (PA). The V_G should be biased on one side of the PA. The V_{D3} must be biased on both sides of the PA. The V_{D1} and V_{D2} should only be biased on one side of the PA. The PA is biased typically with $V_G = -0.9$ V and $V_D = 8$ V.

The bias (V_{G1} , V_{G2} , V_{G3}) should always be applied before the drain voltage (V_{D1} , V_{D2} , V_{D3}) is applied and when switching off the PA the drain voltage must be switched off first before the gate voltage. It is strongly recommended to pulse the drain voltage of the PA so the heat can be dissipated from the device.

Note 2 - Bias Arrangement

Each DC pin (V_D and V_G) needs to have DC bypass capacitance of 100 pF as close to the device as possible. In addition the V_G must have 2.2 μ F on the side the gate voltage is applied. It is recommended to also use a further capacitance of 0.01 μ F on the DC pins.

Note 3 - Pulse Operation

The performance of the MAAP-015024 is characterized under pulsed conditions with a pulse width of 5 μ S and a duty cycle of 5%. The measurements were taken while the drain voltage was pulsed. It is strongly recommended to ensure the heat generated is dissipated from the die with an adequate thermal solution. If this thermal path is not provided this will result in reduced performance/lifetime and possible thermal runaway that will permanently damage the PA. It is not recommended to operate this PA in CW operation unless the bias is reduced.

Applications Section

Handling and Assembly

Die Attachment

This product is 0.075 mm (0.003") thick and has vias through to the backside to enable grounding to the circuit. Microstrip substrates should be brought as close to the die as possible. The mounting surface should be clean and flat. If using conductive epoxy, recommended epoxies are Tanaka TS3332LD, Die Mat DM6030HK or DM6030HK-Pt cured in a nitrogen atmosphere per manufacturer's cure schedule. Apply epoxy sparingly to avoid getting any on to the top surface of the die. An epoxy fillet should be visible around the total die periphery. For additional information please see the MACOM "Epoxy Specifications for Bare Die" application note. If eutectic mounting is preferred, then a flux-less gold-tin (AuSn) preform, approximately 0.0012 thick, placed between the die and the attachment surface should be used. A die bonder that utilizes a heated collet and provides scrubbing action to ensure total wetting to prevent void formation in a nitrogen atmosphere is recommended. The gold-tin eutectic (80% Au 20% Sn) has a melting point of approximately 280°C (Note: Gold Germanium should be avoided). The work station temperature should be 310°C +/- 10°C. Exposure to these extreme temperatures should be kept to minimum. The collet should be heated, and the die pre-heated to avoid excessive thermal shock. Avoidance of air bridges and force impact are critical during placement.

Wire Bonding

Windows in the surface passivation above the bond pads are provided to allow wire bonding to the die's gold bond pads. The recommended wire bonding procedure uses 0.076 mm x 0.013 mm (0.003" x 0.0005") 99.99% pure gold ribbon with 0.5-2% elongation to minimize RF port bond inductance. Gold 0.025 mm (0.001") diameter wedge or ball bonds are acceptable for DC Bias connections. Aluminium wire should be avoided. Thermo-compression bonding is recommended though thermo-sonic bonding may be used providing the ultrasonic content of the bond is minimized. Bond force, time and ultrasonic's are all critical parameters. Bonds should be made from the bond pads on the die to the package or substrate. All bonds should be as short as possible.

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.