


## Features

- 75 Ohm
- SMT unit
- RoHS\* Compliant

## Description

The MAFL-011018 is a low profile, surface mount filter with 3 transmission paths allowing full triplexer operation. The CATV reverse and forward bands are provided along with a further band meeting the MoCA specification. This filter is specifically designed for CATV and MoCA applications.

## Functional Schematic



## Ordering Information

| Part Number      | Package        |
|------------------|----------------|
| MAFL-011018      | 200 piece reel |
| MAFL-011018-Tray | 480 piece tray |

## Pin Configuration

| Pin Number              | Function     |
|-------------------------|--------------|
| 1                       | MoCA Port    |
| 4                       | Forward Port |
| 7                       | Reverse Port |
| 14                      | Common Port  |
| 2, 3, 5, 6, 8-13, 15-20 | Ground       |

\* Restrictions on Hazardous Substances, European Union Directive 2011/65/EU.

**Electrical Specifications:  $T_A = +25^\circ\text{C}$ ,  $Z_0 = 75 \Omega$**


| Parameter                      | Test Frequency (MHz)                                 | Units | Min.                 | Typ.                 | Max.                 |
|--------------------------------|--|-------|----------------------|----------------------|----------------------|
| Reverse Path Insertion Loss    | 5 - 42   | dB    | —                    | 1.2                  | 1.5                  |
| Reverse Path Rejection         | 54 - 126<br>126 - 1002<br>1125 - 1675<br>1675 - 3000 | dB    | 62<br>64<br>60<br>30 | 65<br>70<br>64<br>50 | —                    |
| Forward Path Insertion Loss    | 54 - 88<br>88 - 860<br>860 - 1002                    | dB    | —                    | 1.50<br>0.75<br>2.75 | 2.00<br>1.50<br>2.75 |
| Forward Path Rejection         | 5 - 42<br>1125 - 1675<br>1675 - 3000                 | dB    | 50<br>43<br>20       | 52<br>45<br>30       | —                    |
| MoCA Path Insertion Loss       | 1125 - 1150<br>1150 - 1650<br>1650 - 1675            | dB    | —                    | 2.8<br>2.5<br>2.5    | 3.0<br>2.7<br>3.0    |
| MoCA Path Rejection            | 5 - 1002<br>2300 - 3000                              | dB    | 49<br>25             | 55<br>35             | —                    |
| Input Return Loss              | 5 - 42<br>54 - 860<br>860 - 1002<br>1125 - 1675      | dB    | 16<br>16<br>12<br>12 | 18<br>18<br>16<br>16 | —                    |
| Isolation - Forward to Reverse | 5 - 38<br>38 - 42<br>54 - 1002                       | dB    | 55<br>50<br>60       | 58<br>52<br>65       | —                    |
| Isolation Forward to MoCA      | 5 - 42<br>54 - 126<br>126 - 1002<br>1125 - 1675      | dB    | 49<br>49<br>49<br>43 | 70<br>70<br>53<br>50 | —                    |

**Recommended Maximum Ratings**


| Parameter             | Absolute maximum |
|-----------------------|------------------|
| RF Power              | 250 mW           |
| DC Current            | 30 mA            |
| Operating temperature | -40°C to +85°C   |
| Storage temperature   | -40°C to +85°C   |



## Application Schematic



## Outline Dimensions




Dimensions are in millimetres.

Tolerance:  $.x \pm 0.1$  mm, except where specified.


The maximum allowable coplanarity measurement between PCB and customer board surface is 0.15mm.

## Typical Performance Curves


Reverse Insertion Loss




Forward Insertion Loss



MoCA Insertion Loss




Common Port Return Loss




## Typical Performance Curves


**Reverse Path**




**Forward Path**




**MoCA Path**



**Reverse to Forward Isolation**




**Forward to MoCA Isolation**




## Tape & Reel Information


| Parameter  | Units | Value |
|--|-------|-------|
| Qty per reel                                       | -     | 200   |
| Reel Size  | mm    | 330   |
| Tape Width   | mm    | 72.0  |
| Pitch  | mm    | 28.0  |
| Ao   | mm    | 23.3  |
| Bo   | mm    | 47.8  |
| Ko   | mm    | 6.8   |
| Orientation  | -     | F54   |
| Reference Application Note ANI-019 for orientation |       |       |



Section B-B



Section A-A



Dimensions are in millimetres.

Tolerance: .x ± 0.1 mm, except where specified.



7

MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit [www.macom.com](http://www.macom.com) for additional data sheets and product information.


For further information and support please visit:  
<https://www.macom.com/support>

## Tray Information

| Parameter   | Units | Value     |
|---|-------|-----------|
| Min Order Qty   | -     | 480       |
| Tray Length   | mm    | 270       |
| Tray Width  | mm    | 200       |
| Height  | mm    | 20.8      |
| Ao  | mm    | 35        |
| Bo  | mm    | 50        |
| Ko  | mm    | 14.4      |
| Orientation   | -     | See below |
| Consecutive trays will be stacked alternately at 180° |       |           |



Section B-B



Section A-A

Dimensions are in millimetres.

Tolerance:  $.x \pm 0.1$  mm, except where specified.



MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.